



**MIDCOM Data  
Technologies, Inc.**  
"Your Business. The Right Solution."

Call Today!  
**(800) 643-2664**



**DCS & Labeling Worldwide**

## The Industrial Thermal Solutions



# CL e Series Printers

Industrial CL e high-speed printers are ideal for:

- Compliance Labeling
- WIP Tracking
- Shipping/Receiving
- Asset Tracking
- WMS
- Logistic Tracking
- Retail Labeling
- Laboratory Labeling
- Pallet Labeling

### Industry Leading Throughput

The CL e Series printers use a fast, powerful 32-Bit RISC processor and high-speed interface to deliver excellent performance at an outstanding value.

### Rugged Industrial Design

The CL e's heavy-duty metal construction, proven reliability, and excellent media handling deliver optimum performance in the most demanding environments.

### Connectivity and Application Flexibility

The CL408 e/CL412 e and CL608 e/CL612 e printers simplify connectivity with seven options of user configurable Plug-In Interface Modules. For centralized printer management and administration, the CL e Series offers 10/100 Ethernet (wired) and wireless (802.11g) interface solutions.



Performs best with  
**Techno**  
T H E R M  
Labels & Ribbons

# SPECIFICATIONS



	CL408 e	CL412 e	CL608 e	CL612 e
Printing Method	Direct Thermal, Thermal Transfer			
Print Resolution	203 dpi (8 dpmm)	305 dpi (12 dpmm)	203 dpi (8 dpmm)	305 dpi (12 dpmm)
Print Speed	6 ips (150 mm/s)		8 ips (200 mm/s)	
Media Size	Max. 5.1" (131 mm) W Min 0.87" (22 mm) W x 0.24" (6 mm) L		Max. 7" (178 mm) W Min. 1.96" (50 mm) W x 0.78" (20 mm) L	
Max. Print Width	4.1" (104 mm)		6" (152 mm)	6.5" (164 mm)
Max. Print Length	49.2" (1249 mm)	32.8" (833 mm)	49.2" (1249 mm)	32.8" (833 mm)
Max. Ribbon Size	4.4" (111 mm) W x 1475' (450 m) L; Face-In		6.75" (172 mm) W x 1345' (410 m) L; Face-In	
Dimensions	10.7" (271 mm) W x 16.9" (430 mm) D x 12.6" (321 mm) H		13.8" (352 mm) W x 16.9" (430 mm) D x 11.7" (298 mm) H	
Weight	28.7 lbs (13 kg)		41.9 lbs (19 kg)	

## Memory:

- 16 MB Standard RAM
- 2 MB Standard Flash
- 4 MB Flash - Optional
- 1 MB or 256k PCMCIA - Optional

## Processor:

32-BIT RISC

## Media:

Roll-fed or fan-fold, die-cut or continuous direct thermal (thermal transfer) labels, synthetics, and tag stock with or without black mark, gap, or notch.

Max. Caliper: 0.01" (0.25 mm)  
Max. Roll Diameter: 8.6" (218 mm)  
Wind: Face-In

## Sensing:

- Adjustable transmissive sensor for gap
- Reflective sensor for black mark
- Automatic, programmable top of form
- Label present sensor (opt. w/dispenser)
- Ribbon-out sensor

## Plug-In Interface Modules:

- Serial - RS232 (up to 57.6k bps)
- Parallel - IEEE1284 (ECP)
- Ethernet - 10/100BaseT
- Wireless 802.11g
- Twinax/Coax
- RS422/485
- USB

## Barcode Symbolologies:

**Linear:** UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet™, GS1-128, GS1-DataBar™

**2-Dimensional:** PDF417, Micro PDF417, Truncated PDF417, Maxicode™, Data Matrix, QR Code, Composite Symbology

## Fonts:

Bitmap - 12 proportional, mono-spaced and outline fonts (Code table 858). Scalable Internal CG Triumvirate® and CG Times® fonts. Optional Downloaded TrueType® fonts, scalable from 8 to 72 points

## Barcode and font formatting:

- 360° rotation of barcodes and text
- Horizontal and vertical character expansion
- Sequential numbering
- Form overlay for high-speed editing of complex formats

## Graphic Support:

Printing and storage of \*.PCX, \*.BMP format, SATO Hex/binary

## Software:

- 32 and 64-bit Windows® Drivers (Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008 and Windows 7)
- Label Software (Label Gallery Free)
- Printer Utilities

## Electrical Requirements:

115V/220V (± 10%), 50/60 Hz (± 1%)  
(Jumper switch required for CL4e, auto-switching for CL6e)

## Agency Certifications:


CE, UL, CSA, TÜV

## Environmental Requirements:


Operating: 41° to 104°F (5° to 40°C)  
15-85% RH, non-condensing  
Storage: 23° to 140°F (-5° to 60°C)  
Max. 90% RH, non-condensing  
EDS: 8kV

## Optional Features:

- Label Cutter
- Label Rewinder
- Memory Expansion
- Plug-In Interface
- Label Gallery
- Label Dispenser
- Internal Rewinder
- Real Time Clock
- RFID (CL4xxe)



Memory expansion



Plug-In Interface Modules



Dispenser



Rewinder

## MIDCOM Data Technologies, Inc.

Main Office  
33493 W. 14 Mile Road, Suite 150  
Farmington Hills, MI 48331-1587  
Toll-Free: (800) 643-2664  
Phone: (248) 661-0100  
info@midcomdata.com