

DASCOM



**MIDCOM Data
Technologies, Inc.**
"Your Business. The Right Solution."

SOLUTIONS FOR BUSINESS PRINTING

Call Today!
(800) 643-2664

T2150

Fast, reliable class leading printers



Tally

- Print speeds up to 900 cps
- 26,000 pages per month workload
- 80 columns
- 24 pin print head produces excellent print quality
- Automatic gap adjustment and quick tear
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

The T2150 and T2250 are highly featured, reliable and stylish machines. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. If 'tear at top of form' is inadequate for your application, the T2150S features a cutting device which separates forms automatically.

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Available Configuration:

T2150 Standard Product

T2150S with Automatic Cutter

LA550N DEC Compatible Version

T2150 IGP with IGP/PJL Support

T2150S with Automatic Cutter and IGP/PJL Support

(800) 643-2664 | www.midcomdata.com

SERIAL MATRIX
PRINTERS

MOBILE
PRINTERS

THERMAL
PRINTERS

LINE MATRIX
PRINTERS

LASER
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE



T2150

Print Speed	High Speed Draft: 15cpi->900cps 12cpi->720cps 10cpi->600cps
Resolution	Up to 360 x 360dpi
Printhead Life	400 million characters
Memory	128Kb
Standard Connectivity	Parallel (bi-directional) and serial RS232
Optional Connectivity	Serial current loop (20mA), Ethernet 10/100 Base T, USB Parallel Adapter
Standard Emulation	IBM proprinter XL24, Epson LA2550, Tally MTPL + barcode + LCP IGP Version: IGP/PGL, Code V, MT660, Printronix, P6000,HP2564C
Optional Emulation	DEC LA75; MT50 (Downloadable from www.dascom.com)
Fonts	HS draft (sans serif), draft (sans serif), Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 barcodes and large character printing. Range of Arabic fonts (Arabic model)
Consumables	Ribbon: 3.6 million characters
STD Paper Handling	Push tractors with paper parking and automatic gap adjustment (AGA).
Opt'l Paper Handling	Cut sheet front insertion with AGA Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder. Paper cutting device (2150S only)
Paper Type	Continuous forms, Cut sheet
Paper Weight	Continuous forms 60-120gsm; Cut sheet 80-120gsm
Paper Size	3" - 10" width; 3" - 22" length
Physical Weight	Approximately 22lbs
Physical Size	(HxWxD): 16.7" x 11.8" x 15.7"
Power Voltage	AC 120V or 220-240V
Power Consumption	40W printing
Workload	26,000 pages per month
Number of Copies	Up to 6 part forms
Temperature	+10° to +35°C
Humidity	20% to 80%
Acoustic	53dB(A)
Warranty	1 year return to depot